



MEGA-PLUS

PRESSURE TANK

MegaPlus Pressure tank is an essential part of a pressurized water system that provides water pressure at a set level. The tank stores supplemental water between diaphragm and liner, and the pressurized air chamber is able to create a supply circle. This process reduces the number of times the motor need to start in order for the system pressure to remain at the set level.

The tension of diaphragm maintains water pressure within the system, ensuring proper operation of the dishwasher and washing machine, and robust flow for showering and bathing. MegaPlus provides high water pressure solution for the high rise building and the long distance pressure support. Insuring the water system works efficiently and energy saving with no maintenance.



Lead-Free



AQUASKY • SAFE • STABILITY



2025/12/29 Update

MEGAPLUS PRESSURE TANK

Model Number	Total Tank Volume		Diameter		Height (Base Including)		Box Length		Box Width		Box Height		N.W.		G.W.		Shipping Volume	Connection
	Liter	Gal	Cm	Inch	Cm	Inch	Cm	Inch	Cm	Inch	Cm	Inch	Kg	Lbs.	Kg	Lbs.	CUF	
MEGA-2	2	0.5	12.3	4.8	21.4	8.4	27.4	10.8	27.0	10.6	24.0	9.4	3.2	7.0	3.62	7.9	0.63	1"
MEGA-3	3	0.8	14.0	5.5	21.0	8.3	31.0	12.2	31.0	12.2	24.0	9.4	4.5	9.9	5.1	11.2	0.81	1"
MEGA-8	8	2.0	20.3	8.0	30.1	11.9	21.0	8.3	21.0	8.3	32.0	12.6	2.3	5.1	2.7	6.0	0.50	1"
MEGA-18	18	4.5	28.0	11.0	36.5	14.4	28.0	11.0	28.0	11.0	39.0	15.4	4.7	10.4	5.1	11.2	1.08	1"
MEGA-24	24	6.0	29.0	11.4	40.7	16.0	31.0	12.2	31.0	12.2	42.0	16.5	4.9	10.8	5.8	12.8	1.42	1"
MEGA-40	40	10.0	29.0	11.4	56.4	22.2	31.0	12.2	31.0	12.2	58.0	22.8	6.1	13.4	7.0	15.4	1.97	1"

Stand Models With Base

MEGA-60	60	14	39.0	15.4	60.7	23.9	40.0	15.7	40.0	15.7	62.0	24.4	13.1	28.9	14.4	31.7	3.50	1"
MEGA-80	80	20	39.0	15.4	79.2	31.2	41.0	16.1	41.0	16.1	80.0	31.5	18.6	41.0	20.1	44.3	4.75	1"
MEGA-100	100	28	39.0	15.4	95.6	37.6	40.0	15.7	40.0	15.7	98.0	38.6	22.2	48.9	24.0	52.9	5.54	1"
MEGA-120	120	32	39.0	15.4	113.9	44.8	40.0	15.7	40.0	15.7	116.8	46.0	24.1	53.1	26.7	58.9	6.60	1"
MEGA-130	130	34	55.0	21.7	77.9	30.7	55.0	21.7	55.0	21.7	79.0	31.1	24.0	52.9	27.0	59.5	8.44	1-1/4"
MEGA-160	160	44	55.0	21.7	92.7	36.5	55.0	21.7	55.0	21.7	94.0	37.0	30.7	67.7	34.0	75.0	10.04	1-1/4"
MEGA-200	200	53	55.0	21.7	104.3	41.1	55.0	21.7	55.0	21.7	108.0	42.5	34.7	76.5	38.0	83.8	11.53	1-1/4"
MEGA-240	240	62	55.0	21.7	118.7	46.7	55.0	21.7	55.0	21.7	120.0	47.2	43.7	96.3	46.5	102.5	12.81	1-1/4"
MEGA-300	300	81	55.0	21.7	145.5	57.3	55.0	21.7	55.0	21.7	149.0	58.7	55.0	121.3	61.0	134.5	15.91	1-1/4"
MEGA-450	450	120	65.0	25.6	140.6	55.4	65.0	25.6	65.0	25.6	144.0	56.7	65.7	144.8	70.7	155.9	21.48	1-1/4"

SHELL	SYSTEM CONNECTION	COATING	DIAPHRAGM
Cold Rolled Carbon Steel	304 Stainless Steel Connector	Triple Grade Blue Paint	Heavy-Duty Butyl Rubber
LINER MATERIAL	FACTORY PRE-CHARGE	MAX WORKING TEMPERATURE	MAX WORKING PRESSURE
FDA Grade Polypropylene	4 Bar / 58 PSI	90 °C / 194 °F	16 Bar / 232 PSI



SHIELD COATING



N2 FILLING



AQUASKY PLUS



www.aquaskyplus.com

AQUASKY ENTERPRISE CORP.

No. 36, Ln. 212, Sec. 1, Hemu Rd., Shengang Dist., Taichung City 429, Taiwan

TEL 886-4-2562-6368 FAX 886-4-2561-6332